

**This Page is Inserted by IFW Indexing and Scanning
Operations and is not part of the Official Record**

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ **BLACK BORDERS**
- ☐ **IMAGE CUT OFF AT TOP, BOTTOM OR SIDES**
- ☐ **FADED TEXT OR DRAWING**
- ☐ **BLURRED OR ILLEGIBLE TEXT OR DRAWING**
- ☐ **SKEWED/SLANTED IMAGES**
- ☐ **COLOR OR BLACK AND WHITE PHOTOGRAPHS**
- ☐ **GRAY SCALE DOCUMENTS**
- ☐ **LINES OR MARKS ON ORIGINAL DOCUMENT**
- ☐ **REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY**
- ☐ **OTHER:** _____

IMAGES ARE BEST AVAILABLE COPY.

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.

PATENT ABSTRACTS OF JAPAN

(11)Publication number : 59-128774

(43)Date of publication of application : 24.07.1984

1)Int.Cl.

H01M 6/44

H01M 2/02

1)Application number : 58-003303

(71)Applicant : FUJI ELELCTROCHEM CO LTD

2)Date of filing : 14.01.1983

(72)Inventor : YAMAMOTO KOHEI


MURAI MITSUYOSHI

4) MANUFACTURE OF BATTERY

7)Abstract:

PURPOSE: To simply manufacture a special battery having desired voltage, rated capacity, and dimension by separating a container and a cover which are formed in one body by a blow forming process from a connecting part and again bonding the cover to the container after a unit cell assembly is accommodated in it.

CONSTITUTION: A hollow forming body 1 having a specified dimension is formed by a blow forming process. A connecting part 12 is cut and rimmed, then a container 10 and a cover 14 are separated. An assembly 22 prepared by arranging a plurality of unit cells 30 on a tray 28 is accommodated in the container 10 and the assembly is connected to terminals 20 with lead wires 24. Molten wax or foamable resin solution is filled in the container. An adhesive 34 is spreaded in the outside of a seal part 10A and the cover 14 is fit to the container 10 to form a cylindrical battery.



GAL STATUS

Date of request for examination]

Date of sending the examiner's decision of rejection]

Kind of final disposal of application other than the
examiner's decision of rejection or application
converted registration]

Date of final disposal for application]

Patent number]


Date of registration]

Number of appeal against examiner's decision of
ejection]

Date of requesting appeal against examiner's
ecision of rejection]

Date of extinction of right]

Copyright (C); 1998,2000 Japan Patent Office



The Delphion
Integrated
View

Other Views:
INPADOC

Title: **JP59128774A2: MANUFACTURE OF BATTERY**
 ► Want to see a more descriptive title highlighting what's new about this invention?

Country: **JP Japan**
 Kind: **A**

Inventor(s): **YAMAMOTO KOHEI**
MURAI MITSUYOSHI

Applicant/Assignee: **FUJI ELELCTROCHEM CO LTD**



News, Profiles, Stocks and More about this company

Issued/Filed Dates: **July 24, 1984 / Jan. 14, 1983**

Application Number: **JP1983000003303**

IPC Class: **H01M 6/44; H01M 2/02;**

Priority Number(s): **Jan. 14, 1983 JP1983000833303**

Abstract:

Purpose: To simply manufacture a special battery having desired voltage, rated capacity, and dimension by separating a container and a cover which are formed in one body by a blow forming process from a connecting part and again bonding the cover to the container after a unit cell assembly is accommodated in it.

Constitution: A hollow forming body 1 having a specified dimension is formed by a blow forming process. A connecting part 12 is cut and trimmed, then a container 10 and a cover 14 are separated. An assembly 22 prepared by arranging a plurality of unit cells 30 on a tray 28 is accommodated in the container 10 and the assembly is connected to terminals 20 with lead wires 24. Molten wax or foamable resin solution is filled in the container. An adhesive 34 is spreaded in the outside of a seal part 10A and the cover 14 is fit to the container 10 to form a cylindrical battery.


COPYRIGHT: (C)1984,JPO&Japio

► See a clear and precise summary of the whole patent, in understandable terms.

Family: Show known family members

Other Abstract Info: none


Foreign References: No patents reference this one



[View Image](#)

1 page





Nominate this
for the Gallery...

[Subscribe](#) | [Privacy Policy](#) | [Terms & Conditions](#) | [FAQ](#) | [Site Map](#) | [Help](#) | [Contact Us](#)
© 1997 - 2002 Delphion Inc.